

How to Obfuscate Programs Directly

Joe Zimmerman

Program Obfuscation

- Goal: make a program P “unintelligible” while preserving its functionality [BGI+01]

Program Obfuscation

- Goal: make a program P “unintelligible” while preserving its functionality [BGI+01]
- Extremely powerful primitive

Program Obfuscation

- Goal: make a program P “unintelligible” while preserving its functionality [BGI+01]
- Extremely powerful primitive
- Gold standard: Virtual Black-Box (VBB) security [BGI+01]
 - Obfuscated program $O(P)$ no better than oracle access

Program Obfuscation

- Goal: make a program P “unintelligible” while preserving its functionality [BGI+01]
- Extremely powerful primitive
- Gold standard: Virtual Black-Box (VBB) security [BGI+01]
 - Obfuscated program $O(P)$ no better than oracle access
- Weaker definition: indistinguishability obfuscation (iO) [BGI+01]

Program Obfuscation

- Several candidate obfuscators known
[GGH+13b, BR14, BGK+14, PST14, GLSW14, AGIS14, MSW14]

Program Obfuscation

- Several candidate obfuscators known
[GGH+13b, BR14, BGK+14, PST14, GLSW14, AGIS14, MSW14]
- Fundamental building block: multilinear maps
[BS03, GGH13a, CLT14, GGH14, CLT15]
- VBB security in generic multilinear map model
[GGH+13b, BGK+13]

Program Obfuscation

- In all known constructions, cost remains astronomical
 - Can be improved for some specific function families
[LPS04, Wee05, CD08, CRV10, AGIS14, SZ14]

Program Obfuscation

- In all known constructions, cost remains astronomical
 - Can be improved for some specific function families
[LPS04, Wee05, CD08, CRV10, AGIS14, SZ14]
- Obstacles to efficient general-purpose obfuscation:
 1. Circuits must be converted to matrix branching programs: depth $d \rightarrow$ size 4^d [Bar86]

Program Obfuscation

- In all known constructions, cost remains astronomical
 - Can be improved for some specific function families
[LPS04, Wee05, CD08, CRV10, AGIS14, SZ14]
- Obstacles to efficient general-purpose obfuscation:
 1. Circuits must be converted to matrix branching programs: $\text{depth } d \rightarrow \text{size } 4^d$ [Bar86]
 2. Known multilinear maps have “noise” parameter that grows with the degree

This work

- In all known constructions, cost remains astronomical
 - Can be improved for some specific function families
[LPS04, Wee05, CD08, CRV10, AGIS14, SZ14]
- Obstacles to efficient general-purpose obfuscation:
 - ~~1. Circuits must be converted to matrix branching programs: depth $d \rightarrow$ size 4^d [Bar86]~~
 2. Known multilinear maps have “noise” parameter that grows with the degree

This work

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs

This work

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- Evaluation of obfuscated circuit mirrors structure of original

This work

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- Evaluation of obfuscated circuit mirrors structure of original
- Number of ring ops polynomial in original circuit size

This work

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- Evaluation of obfuscated circuit mirrors structure of original
- Number of ring ops polynomial in original circuit size

	Degree of multilinearity	Obfuscation size (# ring elements)	Evaluation time (# ring operations)
Via Barrington's Thm. [GGH ⁺ 13b, BR14, BGK ⁺ 14]	$O(4^d n + n^2)$	$O(4^d n + n^2)$	$O(4^d n + n^2)$
[AGIS14]	$O(2^d n + n^2)$	$O(8^d n + n^2)$	$O(8^d n + n^2)$
[AGIS14] + [Gie01]	$O(2^{(1+\varepsilon)d} n + n^2)$	$O(2^{(1+\varepsilon)d} 4^{2/\varepsilon} n + n^2)$	$O(2^{(1+\varepsilon)d} 4^{2/\varepsilon} n + n^2)$
This work	$O(2^d n + n^2)$	$O(d^2 s^2 + n^2)$	$O(d^2 s^2 + n^2)$

Performance for circuits of input length n , size s , and depth d .

This work

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- Evaluation of obfuscated circuit mirrors structure of original
- Number of ring ops polynomial in original circuit size
- Prove VBB obfuscation in generic model

	Degree of multilinearity	Obfuscation size (# ring elements)	Evaluation time (# ring operations)
Via Barrington's Thm. [GGH ⁺ 13b, BR14, BGK ⁺ 14]	$O(4^d n + n^2)$	$O(4^d n + n^2)$	$O(4^d n + n^2)$
[AGIS14]	$O(2^d n + n^2)$	$O(8^d n + n^2)$	$O(8^d n + n^2)$
[AGIS14] + [Gie01]	$O(2^{(1+\varepsilon)d} n + n^2)$	$O(2^{(1+\varepsilon)d} 4^{2/\varepsilon} n + n^2)$	$O(2^{(1+\varepsilon)d} 4^{2/\varepsilon} n + n^2)$
This work	$O(2^d n + n^2)$	$O(d^2 s^2 + n^2)$	$O(d^2 s^2 + n^2)$

Performance for circuits of input length n , size s , and depth d .

This work

- For “noisy” maps [GGH13a, CLT13, GGH14, CLT15]:
concrete efficiency improvements
 - Due to noise, cost of ring operations is still $\exp(d)$
 - Still requires FHE for P/poly

This work

- For “noisy” maps [GGH13a, CLT13, GGH14, CLT15]: concrete efficiency improvements
 - Due to noise, cost of ring operations is still $\exp(d)$
 - Still requires FHE for P/poly
- For “clean” maps (open problem): obfuscation for P/poly would now be practical!
 - “Noise” not inherent – central open problem

This work

- For “noisy” maps [GGH13a, CLT13, GGH14, CLT15]: concrete efficiency improvements
 - Due to noise, cost of ring operations is still $\exp(d)$
 - Still requires FHE for P/poly
- For “clean” maps (open problem): obfuscation for P/poly would now be practical!
 - “Noise” not inherent – central open problem
- Concurrent work:
 - [AB15]: also obfuscates circuits without converting to branching programs; achieves iO in generic model

Background: multilinear maps

- Fundamental tool for obfuscation

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices
- Supports the following operations:

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices
- Supports the following operations:
 $\text{Setup}() \rightarrow (\text{pp}, \text{sp})$

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices
- Supports the following operations:

$\text{Setup}() \rightarrow (\text{pp}, \text{sp})$

$\text{Encode}(\text{sp}, x, S) \rightarrow [x]_S \quad (\text{where } S \subset U)$

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices
- Supports the following operations:

$\text{Setup}() \rightarrow (\text{pp}, \text{sp})$

$\text{Encode}(\text{sp}, x, S) \rightarrow [x]_S$ (where $S \subset U$)

$\text{Add}(\text{pp}, [x]_S, [y]_S) \rightarrow [x+y]_S$ (arithmetic mod N)

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices
- Supports the following operations:

$\text{Setup}() \rightarrow (\text{pp}, \text{sp})$

$\text{Encode}(\text{sp}, x, S) \rightarrow [x]_S$ (where $S \subset U$)

$\text{Add}(\text{pp}, [x]_S, [y]_S) \rightarrow [x+y]_S$ (arithmetic mod N)

$\text{Mult}(\text{pp}, [x]_S, [y]_T) \rightarrow [xy]_{S \cup T}$ (where $S \cup T \subset U$)

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices
- Supports the following operations:

$\text{Setup}() \rightarrow (\text{pp}, \text{sp})$

$\text{Encode}(\text{sp}, x, S) \rightarrow [x]_S$ (where $S \subset U$)

$\text{Add}(\text{pp}, [x]_S, [y]_S) \rightarrow [x+y]_S$ (arithmetic mod N)

$\text{Mult}(\text{pp}, [x]_S, [y]_T) \rightarrow [xy]_{S \cup T}$ (where $S \cup T \subset U$)

$\text{ZeroTest}(\text{pp}, [x]_U) \rightarrow \begin{array}{ll} \text{“zero”} & \text{if } x = 0, \\ \text{“nonzero”} & \text{otherwise} \end{array}$

Background: multilinear maps

- Fundamental tool for obfuscation
- Asymmetric, composite-order [CLT13, GLW14, CLT15]
- Modulus $N = N_1 \dots N_k$, multi-set U of formal indices

- Supports the following operations:

Setup() \rightarrow (pp, sp)


Encode(sp, x, S) \rightarrow $[x]_S$ (where $S \subset U$)

Add(pp, $[x]_S$, $[y]_S$) \rightarrow $[x+y]_S$ (arithmetic mod N)

Mult(pp, $[x]_S$, $[y]_T$) \rightarrow $[xy]_{S \cup T}$ (where $S \cup T \subset U$)

ZeroTest(pp, $[x]_U$) \rightarrow “zero” if $x = 0$,
“nonzero” otherwise

“ST”
(product notation)



Background: multilinear maps

– Example:

$$x = \text{Encode}(\text{sp}, 2, \text{AB}) = [2]_{\text{AB}}$$

Background: multilinear maps

– Example:

$$x = \text{Encode}(\text{sp}, 2, AB) = [2]_{AB}$$

$$y = \text{Encode}(\text{sp}, 3, BC) = [3]_{BC}$$

Background: multilinear maps

– Example:

$$x = \text{Encode}(\text{sp}, 2, AB) = [2]_{AB}$$

$$y = \text{Encode}(\text{sp}, 3, BC) = [3]_{BC}$$

$$z = \text{Encode}(\text{sp}, -6, AB^2C) = [-6]_{AB^2C}$$

Background: multilinear maps

– Example:

$$x = \text{Encode}(\text{sp}, 2, AB) = [2]_{AB}$$

$$y = \text{Encode}(\text{sp}, 3, BC) = [3]_{BC}$$

$$z = \text{Encode}(\text{sp}, -6, AB^2C) = [-6]_{AB^2C}$$

$$w = \text{Mult}(\text{pp}, x, y) = [2]_{AB} * [3]_{BC} = [6]_{AB^2C}$$

Background: multilinear maps

– Example:

$$x = \text{Encode}(\text{sp}, 2, AB) = [2]_{AB}$$

$$y = \text{Encode}(\text{sp}, 3, BC) = [3]_{BC}$$

$$z = \text{Encode}(\text{sp}, -6, AB^2C) = [-6]_{AB^2C}$$

$$w = \text{Mult}(\text{pp}, x, y) = [2]_{AB} * [3]_{BC} = [6]_{AB^2C}$$

$$\text{ZeroTest}(\text{pp}, \text{Add}(\text{pp}, z, w)) = \text{“zero”}$$

Background: multilinear maps

– Example:

$$x = \text{Encode}(\text{sp}, 2, AB) = [2]_{AB}$$

$$y = \text{Encode}(\text{sp}, 3, BC) = [3]_{BC}$$

$$z = \text{Encode}(\text{sp}, -6, AB^2C) = [-6]_{AB^2C}$$

$$w = \text{Mult}(\text{pp}, x, y) = [2]_{AB} * [3]_{BC} = [6]_{AB^2C}$$

$$\text{ZeroTest}(\text{pp}, \text{Add}(\text{pp}, z, w)) = \text{“zero”}$$

(assuming AB^2C is the top-level index set U)

Background: multilinear maps

- Security definition:
 - Intuitively, encodings $[x]_s$ hide original scalars x in Z_N
 - Formally: generic model only exposes map operations
[GGH+13a, BR13, BGK+13]
 - See paper for details

Background: multilinear maps

- Security definition:
 - Intuitively, encodings $[x]_s$ hide original scalars x in Z_N
 - Formally: generic model only exposes map operations
[GGH+13a, BR13, BGK+13]
 - See paper for details
- Note: zero-testing only possible at the top index set U
 - Stronger model: adversary can zero-test anywhere

Background: multilinear maps

- Security definition:
 - Intuitively, encodings $[x]_s$ hide original scalars x in Z_N
 - Formally: generic model only exposes map operations
[GGH+13a, BR13, BGK+13]
 - See paper for details
- Note: zero-testing only possible at the top index set U
 - Stronger model: adversary can zero-test anywhere
 - Captures deterministic encodings

Background: multilinear maps

- Security definition:
 - Intuitively, encodings $[x]_s$ hide original scalars x in Z_N
 - Formally: generic model only exposes map operations [GGH+13a, BR13, BGK+13]
 - See paper for details
- Note: zero-testing only possible at the top index set U
 - Stronger model: adversary can zero-test anywhere
 - Captures deterministic encodings
 - Generic transformation [BWZ14]:

Background: multilinear maps

- Security definition:
 - Intuitively, encodings $[x]_s$ hide original scalars x in Z_N
 - Formally: generic model only exposes map operations [GGH+13a, BR13, BGK+13]
 - See paper for details
- Note: zero-testing only possible at the top index set U
 - Stronger model: adversary can zero-test anywhere
 - Captures deterministic encodings
 - Generic transformation [BWZ14]:
 - If M is secure with zero-testing only at U , then M' is secure with arbitrary zero-testing

Background: multilinear maps

- Security definition:
 - Intuitively, encodings $[x]_s$ hide original scalars x in \mathbb{Z}_N
 - Formally: generic model only exposes map operations [GGH+13a, BR13, BGK+13]
 - See paper for details
- Note: zero-testing only possible at the top index set U
 - Stronger model: adversary can zero-test anywhere
 - Captures deterministic encodings
 - Generic transformation [BWZ14]:
 - If M is secure with zero-testing only at U ,
then M' is secure with arbitrary zero-testing
 - $M \rightarrow M'$ adds only two components to modulus N

Background: multilinear maps

- We will make essential use of composite order

Background: multilinear maps

– We will make essential use of composite order

– Direct Product Notation:

For encodings $[x]_S$, with x in $Z_N = Z_{N_1 \dots N_k}$:

write as $[x_1, \dots, x_k]_S$, where $x = x_i \pmod{N_i}$ by CRT

Background: multilinear maps

- We will make essential use of composite order
- Direct Product Notation:
For encodings $[x]_S$, with x in $Z_N = Z_{N_1 \dots N_k}$:
write as $[x_1, \dots, x_k]_S$, where $x = x_i \pmod{N_i}$ by CRT
- Addition and multiplication operate componentwise

Background: multilinear maps

- We will make essential use of composite order
- Direct Product Notation:
For encodings $[x]_S$, with x in $Z_N = Z_{N_1 \dots N_k}$:
write as $[x_1, \dots, x_k]_S$, where $x = x_i \pmod{N_i}$ by CRT
- Addition and multiplication operate componentwise
- $\text{ZeroTest}(\text{pp}, [x_1, \dots, x_k]_U) = \text{"zero"} \iff x_i = 0 \text{ for all } i$

Background: multilinear maps


- We will make essential use of composite order
- Direct Product Notation:
For encodings $[x]_S$, with x in $Z_N = Z_{N_1 \dots N_k}$:
write as $[x_1, \dots, x_k]_S$, where $x = x_i \pmod{N_i}$ by CRT
- Addition and multiplication operate componentwise
- $\text{ZeroTest}(\text{pp}, [x_1, \dots, x_k]_U) = \text{"zero"} \iff x_i = 0 \text{ for all } i$
- Crucial property: adversary does not know N_1, \dots, N_k ,
cannot act independently on components

Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$


Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$



Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$
 - e.g., AES



Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$

Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$
- Boolean output defined by whether $C(x, y) = 0$

Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$
- Boolean output defined by whether $C(x, y) = 0$
- Obfuscation need only hide secret key y

Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$
- Boolean output defined by whether $C(x, y) = 0$
- Obfuscation need only hide secret key y
 - Must be able to evaluate $C(., y)$ given $\text{Obf}_C(y)$

Our construction

- We obfuscate *keyed* arithmetic circuit families $C(x, y)$
- Boolean output defined by whether $C(x, y) = 0$
- Obfuscation need only hide secret key y
 - Must be able to evaluate $C(., y)$ given $\text{Obf}_C(y)$
 - VBB security:
 - “ $\text{Obf}_C(y)$ no better than oracle access to $C(., y)$ ”

Our construction

- Keyed obfuscation $C(., y)$ still general-purpose
(C can be universal circuit)

Our construction

- Keyed obfuscation $C(., y)$ still general-purpose
(C can be universal circuit)
- Avoid universal circuit when possible
 - Obfuscate directly

Our construction

- Keyed obfuscation $C(., y)$ still general-purpose
(C can be universal circuit)
- Avoid universal circuit when possible
 - Obfuscate directly
- Note: often only care about hiding key

Our construction

- Keyed obfuscation $C(\cdot, y)$ still general-purpose
(C can be universal circuit)
- Avoid universal circuit when possible
 - Obfuscate directly
- Note: often only care about hiding key
 - e.g., punctured PRFs [SW14]

Our construction

- Keyed obfuscation $C(., y)$ still general-purpose
(C can be universal circuit)
- Avoid universal circuit when possible
 - Obfuscate directly
- Note: often only care about hiding key
 - e.g., punctured PRFs [SW14]
 - Rich design space of data-oblivious algorithms

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:
 - The circuit C

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:
 - The circuit C
 - 2^n encodings, of the choices $\{0, 1\}$ for each of the n bits of the input x

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:
 - The circuit C
 - 2^n encodings, of the choices $\{0, 1\}$ for each of the n bits of the input x
 - m encodings, one of each bit of the secret y

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:
 - The circuit C
 - 2^n encodings, of the choices $\{0, 1\}$ for each of the n bits of the input x
 - m encodings, one of each bit of the secret y
 - To evaluate $C(x, y)$:

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:
 - The circuit C
 - 2^n encodings, of the choices $\{0, 1\}$ for each of the n bits of the input x
 - m encodings, one of each bit of the secret y
 - To evaluate $C(x, y)$:
 - Select n of the 2^n encodings for the bits of x

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:
 - The circuit C
 - 2^n encodings, of the choices $\{0, 1\}$ for each of the n bits of the input x
 - m encodings, one of each bit of the secret y
 - To evaluate $C(x, y)$:
 - Select n of the 2^n encodings for the bits of x
 - Produce an encoding of $C(x, y)$ using the map's
Add, Mult

Our construction – first attempt

- First idea (not secure):
 - A keyed obfuscation of $C(., y)$ contains:
 - The circuit C
 - 2^n encodings, of the choices $\{0, 1\}$ for each of the n bits of the input x
 - m encodings, one of each bit of the secret y
 - To evaluate $C(x, y)$:
 - Select n of the 2^n encodings for the bits of x
 - Produce an encoding of $C(x, y)$ using the map's Add, Mult
 - Test whether $C(x, y) = 0$ using the map's ZeroTest

Our construction

- Problem 1:

Our construction

- Problem 1:
 - Adversary can evaluate any computation, not just C !

Our construction

- Problem 1:
 - Adversary can evaluate any computation, not just C!
 - Standard approach [GGH+13b]:
 - Convert to branching program [Bar86]
 - “Garble” using Kilian's protocol [Kil88]

Our construction

- Our solution (overview):

Our construction

- Our solution (overview):
 - Composite modulus $N = N_{ev} N_{chk}$

Our construction

- Our solution (overview):

- Composite modulus $N = N_{\text{ev}} N_{\text{chk}}$

- Instead of encodings $[0]$, $[1]$ for each bit,
give out encodings $[0, \alpha]$, $[1, \alpha]$ (CRT notation)

Our construction

- Our solution (overview):
 - Composite modulus $N = N_{\text{ev}} N_{\text{chk}}$
 - Instead of encodings $[0]$, $[1]$ for each bit,
give out encodings $[0, \alpha]$, $[1, \alpha]$ (CRT notation)
 - Evaluation produces $[C(x, y), C(\alpha, \beta)]$ for random
“check” vectors α, β modulo N_{chk}

Our construction

- Our solution (overview):

- Composite modulus $N = N_{\text{ev}} N_{\text{chk}}$
- Instead of encodings $[0], [1]$ for each bit,
give out encodings $[0, \alpha], [1, \alpha]$ (CRT notation)
- Evaluation produces $[C(x, y), C(\alpha, \beta)]$ for random
“check” vectors α, β modulo N_{chk}
- Subtract off *precomputed* encoding $[0, C(\alpha, \beta)]$

Our construction

- Our solution (overview):

- Composite modulus $N = N_{\text{ev}} N_{\text{chk}}$
- Instead of encodings $[0], [1]$ for each bit,
give out encodings $[0, \alpha], [1, \alpha]$ (CRT notation)
- Evaluation produces $[C(x, y), C(\alpha, \beta)]$ for random
“check” vectors α, β modulo N_{chk}
- Subtract off *precomputed* encoding $[0, C(\alpha, \beta)]$

Honest: $[C(x, y), C(\alpha, \beta)] - [0, C(\alpha, \beta)] = [C(x, y), 0]$

Our construction

- Our solution (overview):

- Composite modulus $N = N_{\text{ev}} N_{\text{chk}}$
- Instead of encodings $[0], [1]$ for each bit,
give out encodings $[0, \alpha], [1, \alpha]$ (CRT notation)
- Evaluation produces $[C(x, y), C(\alpha, \beta)]$ for random
“check” vectors α, β modulo N_{chk}
- Subtract off *precomputed* encoding $[0, C(\alpha, \beta)]$

Honest: $[C(x, y), C(\alpha, \beta)] - [0, C(\alpha, \beta)] = [C(x, y), 0]$

Malicious: $[C'(x, y), C'(\alpha, \beta)] - [0, C(\alpha, \beta)]$

Our construction

- Our solution (overview):

- Composite modulus $N = N_{\text{ev}} N_{\text{chk}}$
- Instead of encodings $[0], [1]$ for each bit,
give out encodings $[0, \alpha], [1, \alpha]$ (CRT notation)
- Evaluation produces $[C(x, y), C(\alpha, \beta)]$ for random
“check” vectors α, β modulo N_{chk}
- Subtract off *precomputed* encoding $[0, C(\alpha, \beta)]$

Honest: $[C(x, y), C(\alpha, \beta)] - [0, C(\alpha, \beta)] = [C(x, y), 0]$

Malicious: $[C'(x, y), C'(\alpha, \beta)] - [0, C(\alpha, \beta)]$
 $= [C'(x, y), (C' - C)(\alpha, \beta)]$

Our construction

– Our solution (overview):

- Composite modulus $N = N_{\text{ev}} N_{\text{chk}}$
- Instead of encodings $[0], [1]$ for each bit,
give out encodings $[0, \alpha], [1, \alpha]$ (CRT notation)
- Evaluation produces $[C(x, y), C(\alpha, \beta)]$ for random
“check” vectors α, β modulo N_{chk}
- Subtract off *precomputed* encoding $[0, C(\alpha, \beta)]$

Honest: $[C(x, y), C(\alpha, \beta)] - [0, C(\alpha, \beta)] = [C(x, y), 0]$

Malicious: $[C'(x, y), C'(\alpha, \beta)] - [0, C(\alpha, \beta)]$
 $= [C'(x, y), (C' - C)(\alpha, \beta)]$

- Adversary's C' will not pass ZeroTest unless $C' = C$
(as a polynomial)

Our construction

– Problem 2:

Our construction

- Problem 2:
 - Adversary's computation can be *inconsistent*

Our construction

- Problem 2:
 - Adversary's computation can be *inconsistent*
 - For an input bit x_i , can supply encoding $[0, \alpha]$ on first use in C and $[1, \alpha]$ on second use

Our construction

- Problem 2:
 - Adversary's computation can be *inconsistent*
 - For an input bit x_i , can supply encoding $[0, \alpha]$ on first use in C and $[1, \alpha]$ on second use
 - Cannot be simulated using oracle access to $C(., y)$

Our construction

- Problem 2:
 - Adversary's computation can be *inconsistent*
 - For an input bit x_i , can supply encoding $[0, \alpha]$ on first use in C and $[1, \alpha]$ on second use
 - Cannot be simulated using oracle access to $C(., y)$
- Our solution (overview):

Our construction

- Problem 2:

- Adversary's computation can be *inconsistent*
- For an input bit x_i , can supply encoding $[0, \alpha]$ on first use in C and $[1, \alpha]$ on second use
- Cannot be simulated using oracle access to $C(., y)$

- Our solution (overview):

- Encodings for choices ($x_i = 0$, $x_i = 1$) have different *index sets*

Our construction

- Problem 2:

- Adversary's computation can be *inconsistent*
- For an input bit x_i , can supply encoding $[0, \alpha]$ on first use in C and $[1, \alpha]$ on second use
- Cannot be simulated using oracle access to $C(., y)$

- Our solution (overview):

- Encodings for choices ($x_i = 0$, $x_i = 1$) have different *index sets*
- Introduce auxiliary “interlocking” encodings

Our construction

- Problem 2:

- Adversary's computation can be *inconsistent*
- For an input bit x_i , can supply encoding $[0, \alpha]$ on first use in C and $[1, \alpha]$ on second use
- Cannot be simulated using oracle access to $C(., y)$

- Our solution (overview):

- Encodings for choices ($x_i = 0$, $x_i = 1$) have different *index sets*
- Introduce auxiliary “interlocking” encodings
- Allow completion to top level U *only* for consistent expressions

Our construction

- Resulting algorithm (simplified; iO only):

Our construction

– Resulting algorithm (simplified; iO only):

Using $\text{CM.Encode}(\text{CM.sp}, \cdot)$, for $i \in [n]$, $j \in [m]$, and $b \in \{0, 1\}$, generate the following encoded ring elements:

$$\hat{x}_{i,b} = [b, \alpha_i]_{X_{i,b}} \quad \hat{u}_{i,b} = [1, 1]_{X_{i,b}} \quad \hat{y}_j = [y_j, \beta_j]_Y \quad \hat{v} = [1, 1]_Y$$

$$\hat{z}_{i,b} = [\delta_{i,b}, \gamma_{i,b}]_{X_{i,1-b}^{\deg(x_i)} Z_i W_i} \quad \hat{w}_{i,b} = [0, \gamma_{i,b}]_{W_i}$$

$$\hat{C}^* = [0, C(\alpha_1, \dots, \alpha_n, \beta_1, \dots, \beta_m)]_{Y^{\deg(\mathbf{y})} \prod_{i \in [n]} (X_{i,0} X_{i,1})^{\deg(x_i)} Z_i}$$

Our construction

– Resulting algorithm (simplified; iO only):

Using $\text{CM.Encode}(\text{CM.sp}, \cdot)$, for $i \in [n]$, $j \in [m]$, and $b \in \{0, 1\}$, generate the following encoded ring elements:

$$\hat{x}_{i,b} = [b, \alpha_i]_{X_{i,b}} \quad \hat{u}_{i,b} = [1, 1]_{\underline{X_{i,b}}} \quad \hat{y}_j = [y_j, \beta_j]_Y \quad \hat{v} = [1, 1]_Y$$

$$\hat{z}_{i,b} = [\delta_{i,b}, \gamma_{i,b}]_{\underline{X_{i,1-b}^{\deg(x_i)} Z_i W_i}} \quad \hat{w}_{i,b} = [0, \gamma_{i,b}]_{W_i}$$

$$\hat{C}^* = [0, C(\alpha_1, \dots, \alpha_n, \beta_1, \dots, \beta_m)]_{Y^{\deg(\mathbf{y})} \prod_{i \in [n]} \underline{(X_{i,0} X_{i,1})^{\deg(x_i)} Z_i}}$$

Interlocking index sets

Our construction

- Main theorems:

Our construction

- Main theorems:
 - We prove VBB security in generic model

Our construction

- Main theorems:
 - We prove VBB security in generic model
 - Requires additional techniques (e.g., straddling set systems [BGK+13])

Our construction

- Main theorems:
 - We prove VBB security in generic model
 - Requires additional techniques (e.g., straddling set systems [BGK+13])
 - Simplified version for iO ; better efficiency parameters

Our construction

- Main theorems:
 - We prove VBB security in generic model
 - Requires additional techniques (e.g., straddling set systems [BGK+13])
 - Simplified version for iO ; better efficiency parameters
 - Also define *succinct* obfuscation (size overhead depends only on secret y)

Our construction

- Main theorems:
 - We prove VBB security in generic model
 - Requires additional techniques (e.g., straddling set systems [BGK+13])
 - Simplified version for iO ; better efficiency parameters
 - Also define *succinct* obfuscation (size overhead depends only on secret y)
 - Theorem: “clean” multilinear maps imply succinct obfuscation (assuming hardness of factoring)

Conclusion

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs

Conclusion

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- For “noisy” maps [GGH13a, CLT13, GGH14, CLT15]:
 - Concrete efficiency improvements
 - Remains impractical due to noise blowup

Conclusion

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- For “noisy” maps [GGH13a, CLT13, GGH14, CLT15]:
 - Concrete efficiency improvements
 - Remains impractical due to noise blowup
- For “clean” maps (open problem):
 - Obfuscation for P/poly would now be practical!

Conclusion

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- For “noisy” maps [GGH13a, CLT13, GGH14, CLT15]:
 - Concrete efficiency improvements
 - Remains impractical due to noise blowup
- For “clean” maps (open problem):
 - Obfuscation for P/poly would now be practical!
 - e.g., for AES: 133K ring elements, 281K ring ops

Conclusion

- New construction:
 - Obfuscate general circuits *directly*
 - No matrix branching programs
- For “noisy” maps [GGH13a, CLT13, GGH14, CLT15]:
 - Concrete efficiency improvements
 - Remains impractical due to noise blowup
- For “clean” maps (open problem):
 - Obfuscation for P/poly would now be practical!
 - e.g., for AES: 133K ring elements, 281K ring ops
 - “Noise” not inherent – central open problem